

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 06/21/2023 Date of issue: 06/21/2023

Version: 2.1

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: EZ Off

Product Code: 40200, 42200

1.2. Intended Use of the Product

Iron/Press Cleaner

1.3. Name, Address, and Telephone of the Responsible Party

Faultless Brands

1025 W 8th St.

Kansas City, MO 64101 USA

T: 1-816-842-1230

www.faultless.com

1.4. Emergency Telephone Number

Emergency Number : 1-800-424-9300 (for emergencies) CHEMTREC

*This document is intended to be used for safety in the workplace only, and is not a consumer document.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

STOT SE 3 H335

Full text of H-phrases: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



GHS07

Signal Word (GHS-US) :

Warning

Hazard Statements (GHS-US) :

H335 - May cause respiratory irritation.

Precautionary Statements (GHS-US) :

P261 - Avoid breathing vapors, mist, or spray.

P271 - Use only outdoors or in a well-ventilated area.

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a poison center or doctor if you feel unwell.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US) No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixture

Name	Product Identifier	% (w/w)
Glycerin	(CAS No) 56-81-5	40 - 70
Polyethylene glycol	(CAS No) 25322-68-3	15 - 40

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Stearic acid	(CAS No) 57-11-4	1 - 5
Limestone	(CAS No) 1317-65-3	1 - 5
Triethanolamine	(CAS No) 102-71-6	1 - 5
Citral	(CAS No) 5392-40-5	< 0.1

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Eye Contact: Rinse with plenty of water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting. Rinse mouth. Seek medical attention if a large amount is swallowed.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause respiratory irritation.

Inhalation: May cause respiratory irritation. Symptoms may include: Sore throat. Cough. Burning sensation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Product is not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Thermal decomposition generates: Carbon oxides (CO, CO₂). Acrolein. Nitrogen oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Avoid all unnecessary exposure.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool, and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Peroxides. Polymerization catalysts.

7.3. Specific End Use(s)

Iron/Press Cleaner

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Glycerin (56-81-5)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (mist, total particulate)
		5 mg/m ³ (mist, respirable fraction)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
		3 mg/m ³ (mist-respirable)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³ (mist)
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³ (mist)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
Québec	VEMP (mg/m ³)	10 mg/m ³ (mist)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (mist)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³ (mist)
Yukon	OEL TWA (mg/m ³)	30 mppcf (mist)
		10 mg/m ³ (mist)
Citral (5392-40-5)		
USA ACGIH	ACGIH TWA (ppm)	5 ppm (inhalable fraction and vapor)
USA ACGIH	ACGIH chemical category	dermal sensitizer, Skin - potential significant contribution to overall exposure by the cutaneous route, Not Classifiable as a Human Carcinogen
Manitoba	OEL TWA (ppm)	5 ppm (inhalable fraction and vapor)
Newfoundland & Labrador	OEL TWA (ppm)	5 ppm (inhalable fraction and vapor)
Nova Scotia	OEL TWA (ppm)	5 ppm (inhalable fraction and vapor)
Ontario	OEL TWA (ppm)	5 ppm (inhalable fraction and vapor)

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Prince Edward Island	OEL TWA (ppm)	5 ppm (inhalable fraction and vapor)
Limestone (1317-65-3)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (total dust)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf 10 mg/m ³
Triethanolamine (102-71-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	5 mg/m ³
British Columbia	OEL TWA (mg/m ³)	5 mg/m ³
Manitoba	OEL TWA (mg/m ³)	5 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	5 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	5 mg/m ³
Ontario	OEL TWA (mg/m ³)	3.1 mg/m ³
Ontario	OEL TWA (ppm)	0.5 ppm
Prince Edward Island	OEL TWA (mg/m ³)	5 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	5 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate ventilation to minimize dust concentrations. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Protective clothing. Gloves. Insufficient ventilation: wear respiratory protection.



Hand Protection: In case of repeated or prolonged contact wear gloves.

Eye Protection: Chemical safety goggles.

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink, or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Tan Paste
Odor	: Not available
Odor Threshold	: Not available
pH	: 8.8 (1%)
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: 187 °C (370 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Peroxides. Polymerization catalysts.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO₂). Nitrogen oxides. Acrolein.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

pH: 8.8 (1%)

Serious Eye Damage/Irritation: Not classified

pH: 8.8 (1%)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Symptoms may include: Sore throat. Cough. Burning sensation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Glycerin (56-81-5)	
LD50 Oral Rat	23000 mg/kg
LD50 Dermal Rabbit	> 10 g/kg
LC50 Inhalation Rat	> 570 mg/m ³ (Exposure time: 1 h)
Citral (5392-40-5)	
LD50 Oral Rat	4950 mg/kg
LD50 Dermal Rabbit	2250 mg/kg
Polyethylene glycol (25322-68-3)	
LD50 Oral Rat	47000 mg/kg
LD50 Dermal Rabbit	> 20 ml/kg
Triethanolamine (102-71-6)	
LD50 Oral Rat	6400 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
Stearic acid (57-11-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Triethanolamine (102-71-6)	
IARC Group	3
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity No additional information available

Glycerin (56-81-5)	
LC50 Fish 1	54000 (51000 - 57000) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Citral (5392-40-5)	
EC50 Daphnia 1	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Triethanolamine (102-71-6)	
LC50 Fish 1	10600 (10600 - 13000) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and Degradability Not available

12.3. Bioaccumulative Potential

Glycerin (56-81-5)	
BCF Fish 1	(no bioaccumulation)
Log Pow	-1.76
Citral (5392-40-5)	
Log Pow	2.76 (at 25 °C)

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Triethanolamine (102-71-6)	
BCF Fish 1	3.9
Log Pow	-2.53

12.4. Mobility in Soil

Stearic acid (57-11-4)	
Log Koc	51.05

12.5. Other Adverse Effects Not available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

EZ Off	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Glycerin (56-81-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
Citral (5392-40-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Polyethylene glycol (25322-68-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Triethanolamine (102-71-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Stearic acid (57-11-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. US State Regulations

Glycerin (56-81-5)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Idaho - Occupational Exposure Limits - TWAs
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs

Citral (5392-40-5)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term

Limestone (1317-65-3)

U.S. - Idaho - Occupational Exposure Limits - TWAs
 RTK - U.S. - Massachusetts - Right To Know List
 U.S. - Michigan - Occupational Exposure Limits - TWAs
 U.S. - Minnesota - Hazardous Substance List
 U.S. - Minnesota - Permissible Exposure Limits - TWAs
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs

Polyethylene glycol (25322-68-3)

U.S. - Minnesota - Hazardous Substance List
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term

Triethanolamine (102-71-6)

RTK - U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

EZ Off

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Stearic acid (57-11-4)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

15.3. Canadian Regulations

EZ Off	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Glycerin (56-81-5)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Citral (5392-40-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Limestone (1317-65-3)	
Listed on the Canadian NDSL (Non-Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Polyethylene glycol (25322-68-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Triethanolamine (102-71-6)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Stearic acid (57-11-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 02/12/2024 Updated date on SDS per customer request, to match foreign translation.
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H335	May cause respiratory irritation

Party Responsible for the Preparation of This Document

Faultless Brands: 1-816-842-1230 (for product information); 1-800-424-9300 (for emergencies)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.